



Safety Data Sheet

according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 16.06.2020

Revision number 1.4

Version date: 16.06.2020

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· **Product name:** Gas cartridge propane/butane

· **Product code:** 15683

1.2 Relevant identified uses of the substance or mixture and uses advised against

· **Identified uses of the substance or mixture**

Aerosol

1.3 Details of the supplier of the safety data sheet

Albert Kerbl GmbH

Felizenzell 9

D-84428 Buchbach

www.kerbl.com

Tel.: 0049-(0)8086-933-100

E-Mail: info@kerbl.com

· **Responsible Department:**

Albert Kerbl GmbH

Tel.: 0049-(0)8086-933-104

E-Mail: bm@kerbl.com

1.4 Emergency telephone number:

Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen

c/o HELIOS Klinikum Erfurt Nordhäuser Straße 74

Tel.: (03 61) 73 07 30 - Fax: (03 61) 7 30 73 17

E-Mail: ggiz@ggiz-erfurt.de - Internet: www.ggiz-erfurt.de

2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) Nr. 1272/2008

Aerosol: Aerosol 1 (H222, H229)

2.2 Label elements

Label elements according to Regulation (EC) Nr. 1272/2008 (CLP/GHS)

Hazard pictograms



Flame (GHS 02)

Signal word

Danger



Safety Data Sheet

Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 16.06.2020

Revision number 1.4

Version date: 16.06.2020

Product name: **Gas cartridge propane/butane**

Product code: 15683

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards

· The mixture does not meet the criteria for PBT or vPvB.

3 Composition/information on ingredients

3.2 Mixtures**Hazardous ingredients:**

CAS: 75-28-5	Isobutane	<95 %
EC-Nr. 200-857-2	Flam. Gas 1: H220; Press. Gas: H280	
Index-Nr. 601-004-00-0		
CAS: 106-97-8	Butane	<95 %
EC-Nr. 203-448-7	Flam. Gas 1: H220; Press. Gas: H280	
Index-Nr. 601-004-00-0		
CAS: 74-98-6	Propane	<95 %
EC-Nr. 200-827-9	Flam. Gas 1: H220; Press. Gas: H280	
Index-Nr. 601-003-00-5		
CAS: 78-78-4	Isopentane	<2 %
EC-Nr. 201-142-8	Flam. Liq. 1 ; H224 Asp. Tox. 1 ; H304 STOT SE 3 ; H336	
Index-Nr. 601-006-00-1	Aquatic Chronic 2 ; H411 EUH066	
Reg.nr. 01-2119475602-38		

Additional information:

The wording of the listed risk phrases and hazard statements refer to section 16.

4 First aid measures

4.1 Description of first aid measures**· General information:**

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

· Inhalation:

Move to fresh air. If symptoms persist, call a physician.

· Skin contact:

Remove immediately any soiled or splashed garment. Rinse abundantly in the water and in the soap. Clean clothes separately before reusing them. Consult a doctor in case of persistent pain.



Safety Data Sheet

Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 16.06.2020

Revision number 1.4

Version date: 16.06.2020

Product name: Gas cartridge propane/butane

Product code: 15683

· Eye contact:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open. If there is any redness, pain or visual impairment, consult an ophthalmologist.

· Ingestion:

Wash out mouth thoroughly and drink 1-2 glasses of water in small sips.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation of spray mist is irritating to the upper airways.

4.3 Indication of any immediate medical attention and special treatment needed

None

5 Firefighting measures

5.1 Extinguishing media

Suitable methods of extinction - In the event of a fire, use: sprayed water or water mist, foam, multipurpose ABC powder, BC powder, carbon dioxide (CO₂)

Unsuitable methods of extinction - In the event of a fire, do not use: water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated.

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke. In the event of a fire, the following may be formed: carbon monoxide (CO), carbon dioxide (CO₂)

5.3 Advice for firefighters

Special protective equipment: Wear self-contained breathing apparatus.

Further information

Cool endangered containers with water spray jet.

Dispose fire residues and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected people away.

Keep people away and stay on the upwind side.

Keep ignition sources away. No smoking.

Consult the safety measures listed under headings 7 and 8.

6.2 Environmental precautions:

Avoid unnecessary release to the environment. Prevent any material from entering drains or waterways. In case of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up:

Collect spillage. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ensure adequate ventilation.

6.4 Reference to other sections

Information regarding safe handling see chapter 7.

Information regarding personal protection see chapter 8.

Information regarding disposal see chapter 13.



Safety Data Sheet

Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 16.06.2020

Revision number 1.4

Version date: 16.06.2020

Product name: **Gas cartridge propane/butane**

Product code: 15683

7 Handling and storage

7.1 Precautions for safe handling

Ensure that there is adequate ventilation, especially in confined areas.
Open and handle container with care.

Fire prevention:

Keep ignition sources away - Do not smoke. Take precautionary measures against static discharges. Pressurized container. Protect from sunlight and temperatures above 50 ° C (eg by Electric lights). Do not open by force or burn even after use. Do not spray in flames or on hot surfaces.

7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements for storage rooms and vessels:

Store in a cool place.

Official regulations on storing pressurized containers must be observed.

Store away from oxidizing agents.

Further information about storage conditions:

Store in tightly closed containers in a cool, dry place.

Protect from heat and direct sunlight.

Ensure adequate ventilation.

Recommended storage temperature: 10-50 ° C

Storage class: No data available.

7.3 Specific end use(s) Keep out of reach of children.

8 Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits		Exposure			
	Country	limit	ml/m ³	mg/m ³	Remarks
78-78-4 Methylbutan	EU	OEL	1000	3000	8 h
	D, TRGS 900	AGW	1000	3000	2(II);DFG, EU
	UK, WEL	TWA	600	1800	8 h
	F, INRS	VME	1000	3000	8 h
106-97-8 Butan	D, TRGS 900	AGW	1000	2400	4(II);DFG
	UK, WEL	TWA	600	1450	8 h
		STEL	750	1810	15 min
	F, INRS	VME	800	1900	8 h
74-98-6 Propan	D, TRGS 900	AGW	1000	1800	4(II);DFG
	UK, WEL	TWA	1000	1800	8 h
75-28-5 Isobutan	D, TRGS 900	AGW	1000	2400	4(II);DFG

8.2 Exposure controls / Personal protection

Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area. Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.



Safety Data Sheet

Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 16.06.2020

Revision number 1.4

Version date: 16.06.2020

Product name: Gas cartridge propane/butane

Product code: 15683

Eye / face protection

Avoid contact with eyes. Use eye protectors designed to protect against liquid splashes. Before handling, wear safety goggles with protective sides in accordance with standard EN166. In the event of high danger, protect the face with a face shield. When spraying, wear a face shield in accordance with standard EN166. Prescription glasses are not considered as protection. Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours. Provide eyewash stations in facilities where the product is handled constantly.

Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact. Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374. Gloves must be selected according to the application and duration of use at the workstation. Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

Skin protection (other than of the hands)

Work clothing worn by personnel shall be laundered regularly. After contact with the product, all parts of the body that have been soiled must be washed.

Respiratory protection

In case of insufficient ventilation, wear respiratory protective equipment with filter.

Thermal hazards

Pressurised container: May burst if heated.

Exposure controls regarding environmental protection

No data available.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

- **General Information**

- **Appearance:**

Form:

Aerosol

Colour:

colourless

- **Odour:**

odourless

- **Smell Threshold:**

not determined

- **pH:**

not determined

- **Change of state**

Melting point/range:

not relevant

Boiling point/range:

-42,1/-11,7/-0,5 °C (Propane/Isobutane/Butane)

- **Flash point:**

-104/-83/-60 °C (Propane/Isobutane/Butane)

- **Flammability (solid, gas):**

not applicable

- **Ignition temperature:**

450/460/365 °C (Propane/Isobutane/Butane)

- **Thermal decomposition:**

not relevant

- **Autoinflammability:**

not self-flammable

- **Explosion hazard:**

Pressurised container: May burst if heated.



Safety Data Sheet

Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 16.06.2020

Revision number 1.4

Version date: 16.06.2020

Product name: **Gas cartridge propane/butane**

Product code: 15683

- **Explosion limits:**
 - Lower:** 1,7/1,5/1,4 Vol.-% (Propane/Isobutane/Butane)
 - Upper:** 10,8/9,4/9,4 Vol.-% (Propane/Isobutane/Butane)
- **Vapour pressure at 20 °C:** 8,33/3,02/2,08 bar (Propane/Isobutane/Butane)
- **Density:** not determined
- **Bulk density** not determined
- **Vapour density** not determined
- **Evaporation rate** not determined
- **Solubility / miscibility**
 - Water:** soluble
- **Partition coefficient (n-Octanol/Water):** not determined
- **Viscosity:** not determined
- **Oxidising properties** not determined

9.2 Other information

No data available.

10 Stability and reactivity

10.1 Reactivity Heating may cause a fire or explosion.**10.2 Chemical stability** This mixture is stable under the recommended handling and storage conditions in section 7.**10.3 Possibility of hazardous reactions** No hazardous reactions when stored under the recommended handling and storage conditions.**10.4 Conditions to avoid:**

Sunlight. High temperatures. Keep away from sources of ignition.

10.5 Incompatible materials: Reacts with strong oxidants.**10.6 Hazardous decomposition products:** None when used as intended.

11 Toxicological information

11.1 Information on toxicological effects**Acute toxicity:****LD/LC50 values relevant for classification:****78-78-4** ISOPENTANE

Oral LD-50 2000 - 5000 mg/kg (Rat)

Inhalation LC50 > 25.3 mg/l (Rat, 4h)

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Eye damage/irritation:

Based on available data, the classification criteria are not met.

Sensitisation, respiratory or skin:

Based on available data, the classification criteria are not met.

Carcinogenicity, germ cell mutagenicity, reproductive toxicity (CMR):

Based on available data, the classification criteria are not met.



Safety Data Sheet

Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 16.06.2020

Revision number 1.4

Version date: 16.06.2020

Product name: **Gas cartridge propane/butane**

Product code: 15683

Specific target organ toxicity (STOT), single/repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional toxicological information:

Inhalation of concentrated vapors as well as oral intake will lead to anesthesia-like conditions and headache, dizziness, etc.

Has a degreasing effect on the skin!

12 Ecological information

12.1 Toxicity**Aquatic Toxicity:****78-78-4 ISOPENTANE**

LC-50 12.8 mg/l (Fish, 96 h)

EC-50 5.2 mg/l (Algae, 96 h)

EC-50 2.3 mg/l (Daphnia, 48h)

12.2 Persistence and degradability Readily biodegradable.**78-78-4 ISOPENTANE**

OECD 301F 71.43 % (28 days)

12.3 Bioaccumulative potential The product is not bioaccumulating.**78-78-4 ISOPENTANE**

Log Pow 2.72

12.4 Mobility in soil No data available.**12.5 Results of PBT and vPvB assessment** The mixture does not meet the criteria for PBT or vPvB.**12.6 Other adverse effects** No data available.

13 Disposal considerations

13.1 Waste treatment methods**Recommendation:**

Must not be disposed together with household garbage. Do not empty into drains.

Must be supplied to an authorized hazardous waste incineration plant, after pretreatment, in accordance with regulations for special waste.

European waste catalog

The listed (n) waste number (s) according to the European Waste Catalogue (EWC), are a recommendation. A final decision must be taken in agreement with the regional waste management company.

16 05 04* gases in pressure containers, containing hazardous substances (including halons)

Uncleaned packaging:**Recommendation:** Disposal according to official regulations.



Safety Data Sheet

Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 16.06.2020

Revision number 1.4

Version date: 16.06.2020

Product name: **Gas cartridge propane/butane**

Product code: 15683

14 Transport information

14.1 UN number

· ADR/RID, ADN, IMDG, ICAO/IATA	UN1950
---------------------------------	--------

14.2 UN proper shipping name

· ADR/RID, ADN	AEROSOLS
IMDG	AEROSOLS
· ICAO/IATA	AEROSOLS, flammable

14.3 Transport hazard class(es)

· ADR/RID, ADN, IMDG, ICAO/IATA	2.1
---------------------------------	-----

Classification code

· ADR/RID, ADN	5F
----------------	----

Special Provisions

· ADR/RID, ADN	190, 327, 344, 625
· IMDG	63, 190, 277, 327, 344, 959
· ICAO/IATA	A145, A167, A802

14.4 Packing group

none

14.5 Environmental hazards

none

14.6 Special precautions for user

EmS	F-D, S-U
-----	----------

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

None

National Regulations

Germany: Water hazard class (WGK)

non-hazardous to water (nwg), Classification according to AwSV

15.2 Chemical safety assessment: No data available



Safety Data Sheet

Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 16.06.2020

Revision number 1.4

Version date: 16.06.2020

Product name: **Gas cartridge propane/butane**

Product code: 15683

16 Other information

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations. The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Revision notes

* Changes since the last version

Abbreviations

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

Title for H and EUH indications (Number and text)

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H224 Extremely flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Methods of evaluating information referred to in Article 9 of Regulation (EC) No 1272/2008 for the purpose of classification

Classification based on the components